

CONTROL

OJ Electronic thermostats are available to control Speedheat floor heating:

MTC-1999-SH

Manual air temperature control

Controls the room temperature with a built-in air sensor.

Supply: 240VAC
Output relay: 3600W / 16A
On/off switch: 2 pole 16A
Dimensions: 115 x 84 x 50mm
Scale range: 10-50 °C
Accuracy: 0.4 °C
Red LED heating indicator
Housing rated IP20
Colour: Off-white
Mounting: flush in a standard vertical wall bracket, or wall box.



MTC-1991-SH

Manual floor temperature control

Controls the floor temperature with a 3m long floor sensor (included). The floor sensor can be extended up to 100m.

Supply: 240VAC
Output relay: 3600W / 16A
On/off switch: 2 pole 16A
Dimensions: 115 x 84 x 50mm
Scale range: 10-50 °C
Accuracy: 0.4 °C
Red LED heating indicator
Housing rated IP20
Colour: Off-white
Mounting: flush in a standard vertical wall bracket, or wall box.



MCD2-1999-SH

Programmable air or floor temperature control

A 4-event programmable time and temperature control, clock type thermostat controls the room temperature with a built-in air sensor OR controls or limits the floor temperature with a 3m long floor sensor (included). The floor sensor can be extended up to 100m.

Supply: 240VAC
Output relay: 3600W / 16A
On/off switch: 2 pole 16A
Dimensions: 115 x 84 x 50mm
Scale range: 5-40 °C
Accuracy: 0.4 °C
Back-lit display
Settings battery backup: 50h
Housing rated Ip21
Colour: Off-white
Mounting: flush in a standard vertical wall bracket, or wall box.



1800 85 75 65

info@speedheat.com.au
www.speedheat.com.au

Control

ETV - 1991

Remote manual floor temperature control

A manual thermostat for DIN rail mounting in the distribution board. Controls the floor temperature with a 3m long floor sensor (included). The floor sensor can be extended up to 100m.

Supply: 240VAC

Output relay: 3600W / 16A

Dimensions: 86 x 36 x 58mm

Scale range: 0-40 °C

Accuracy: 0.4 °C

Setback temperature: 5 °C (activated via 240V signal

From remote timer to terminal 3)

Red LED heating indicator

Housing rated IP20

Colour: Blue and grey

Mounting: on DIN rail



OJ thermostats conform to the relevant CE/EN standards and UL listings. Visit www.oj.dk for further information. OJ Electronic thermostats have a 12 month product guarantee.

TH-0108FS

Programmable air or floor temperature control

A 6-event programmable time and temperature control, clock type thermostat controls the room temperature with a built-in air sensor OR controls or limits the floor temperature with a 3m long floor sensor (included). The floor sensor can be extended up to 100m.

Supply: 240VAC

Output relay: 3600W / 16A

On/off switch: 1 pole 16A

Dimensions: 90 x 125 x 34mm

Scale range: 5-32 °C

Accuracy: 0.5 °C

Colour: White

Mounting: surface on a standard horizontal wall bracket, or wall box.



TERMO CONTACTOR

20A Contactor

Supply: 240VAC

Output relay: 4800W / 20A

Dimensions: 30 x 30 x 30mm

Colour: Black

