

















# TIMBER HEATERS

## LAMINATE & TIMBER PANEL HEATERS (130W/m<sup>2</sup>)

Speedheat laminate & timber heaters have a 6 metre long supply cord, which must be connected to earth and through an earth leakage circuit breaker (RCD or Safety Switch).

	Item No.	Heater Size	Suitable for Room Size	Current (Amps)	Capacity @ 240V
	P 1000/12	2.00 x 4.00m	13-20m <sup>2</sup>	4.5A	1080W
	P 715/12	2.00 x 2.85m	9-14m <sup>2</sup>	3.2A	770W
	P 600/12	1.80 x 2.70m	8-12m <sup>2</sup>	2.7A	650W
	P 550/12	2.00 x 2.20m	7-11m <sup>2</sup>	2.5A	595W
	P 460/12	1.60 x 2.30m	6-9m <sup>2</sup>	2.1A	495W
	P 500/12L	1.00 x 4.00m	7-10m <sup>2</sup>	2.3A	540W
	P 360/12	1.30 x 2.20m	5-7m <sup>2</sup>	1.6A	390W
	P 360/12L	1.00 x 2.85m	5-7m <sup>2</sup>	1.6A	390W
	P 360/12P	0.65 x 4.40m	5-7m <sup>2</sup>	1.6A	390W
	P 275/12	1.00 x 2.20m	4-6m <sup>2</sup>	1.3A	300W
	P 200/12	1.00 x 1.60m	3-4m <sup>2</sup>	0.9A	215W
	P 200/12L	0.65 x 2.45m	3-4m <sup>2</sup>	0.9A	215W
	P 715/12T	1.30 x 2.20m (x2)	12-14m <sup>2</sup>	3.2A	770W
	P 715/12AT	1.0 & 1.6 x 2.2m	12-14m <sup>2</sup>	3.2A	770W
	P 550/12T	1.00 x 2.20m (x2)	9-11m <sup>2</sup>	2.5A	595W
	P 360/12T	0.65 x 2.20m (x2)	6-7m <sup>2</sup>	1.6A	390W



GENERATION4™  
FLOOR HEATING

1800 85 75 65

info@speedheat.com.au  
www.speedheat.com.au

*Timber Heaters*